







A

B

C

D

未注公差/General tolerances (mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
3	6	10	18	30	50	80	120	180	250	315	400	500	>500	±2'
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	

Note:

The A&Z(H) in the name means: A(H) and Z(H).

4	Pin 2	Copper alloy	Sn plated
3	Pin 1	Copper alloy	Sn plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/8	/	300/8
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	/	250/7
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	/	2.5
间距/Pitch(mm)/线数范围/Poles	3.81/N=04~48P		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		





APPD: 兰春华 2022.09.08
CHKD: 龚耀志 2022.09.07
DRFT: 朱岳鹏 2022.09.07

MATERIAL:	SURFACE/COLOR:		
MAT NO./REV:	- / 00		
NAME	15EDGRH-3.81-XXP-1Y-00A&Z(H)		

DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
200029766	CUSTOMER DRAWING	已发布	2:1	1/1

PCB LAYOUT



00			朱岳鹏	2022.09.07
REV	ECN	DESCRIPTION	DRFT	DATE

