

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、集成电路布图设计专有权、商业秘密和未公开信息的所有权利外，其他权利均归本公司所有。

FOR-1755 Rev.1.6


2

3


4

5




6




其他接线方式：形式一：




形式二：



仅Busbar的形式3D展示：



形式三：



尺寸公差 (mm)					0.05/10 ±1'
0	>30	>60	>100	>150	
~30	~60	~100	~150	~150	
±0.20	±0.30	±0.50	±0.70	±1.00	
技术要求/Technical requirements:					
颜色/Color		Black, Orange, Red			
锁紧方式/Locking method		卡扣(Buckle)			
接线方式/Terminal		Busbar, Screw, Crimp, Copper Screw			
外壳材料/Housing material		PA+GF			
接触件材料/Connector material		铜合金 (Copper alloy)			
插入力/Insertion force		100N Max			
拔出力/Withdrawal force		>10N			
插拔次数/Mechanical working life (mating cycles)		100			
安装螺母紧固扭矩/Screw torque		M4/0.4~0.7N.m			
接线规格/Wiring specifications		2/0AWG or 70mm²			
建议剥线长度/Suggested stripping length		19~21mm (Crimp type)			
线径OD/Wire diameter		15.5~17mm (Crimp type)			
额定电压/Rated voltage		1500V DC			
额定电流/Rated current		250A			
绝缘电阻/Insulate resistance		≥5000MΩ (drying)			
耐电压/Withstanding voltage		6800V/min			
接触电阻/Contact resistance		≤0.5mΩ			
过电压等级/Overvoltage category		III			
污染等级/Pollution degree		3			
防护等级/Ingress protection		IP67 (Mated)			
使用温度范围/Operating temperature (°C)		-40~+125 (including temperature rise)			
盐雾/Salt spray		48H			
储存温度/Storage temperature (°C)		-40~+85			
阻燃等级/Flame retardant ability		UL94-V0			
符合RoHS环保要求/Conform to RoHS		Yes			
UL4128认证/UL4128 certification		E526028			
TUV认证/TUV certification		50581738			
满足户外使用/Satisfy outdoor use		Yes			

active

ESS-250A-70-X-XX-00

Color: BK : Black 负极
OR : Orange 正极
RD : Red 正极

Contact Termination: B : Busbar
C : Crimp
S : Screw
B/S : Copper Screw

APPD: 刘剑		2024.01.24	MATERIAL:		SURFACE/COLOR:	
CHKD: 于进海		2024.01.21	MAT NO./REV:		MAT STATUS:	
DRFT: 张晓璐		2021.01.17	NAME		ESS-250A-70-XX-XX-00	
DRAWING NO.		200269869	TYPE		DRAWING STATUS	SHEET
CUSTOMER DRAWING					1:1.25	1/1

01	REV	ECN	DESCRIPTION	DRFT	DATE