

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violators will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 非经书面明确授权, 否则禁止转让、复制、利用、交还本文件的内容, 侵犯者将承担侵权责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。

FOR-1755 Rev.1.3



2

3

4


5

6




Busbar
(适配M5螺钉扭矩: 6N.m)

其他接线方式: 形式一:




Screw
(锁合扭矩: 2-3N.m)


形式二:





仅Busbar的形式3D展示:



形式三:



Copper Screw
(锁合扭矩: 6N.m)



Recommended
Panel Cut-Out

尺寸公差(mm)					0.05/10 ±1'
0	>30	>60	>100	>150	
~30	~60	~100	~150	~150	
±0.20	±0.30	±0.50	±0.70	±1.00	

技术要求/Technical requirements:	
颜色/Color	Black, Orange, Red
锁紧方式/Locking method	卡扣(Buckle)
接线方式/Terminal	Busbar, Screw, Crimp, Copper Screw
外壳材料/Housing material	PA+GF
接触件材料/Connector material	铜合金(Copper alloy)
插入力/Insertion force	100N Max
拔出力/Withdrawal force	>10N
插拔次数/Mechanical working life(mating cycles)	100
安装螺母紧固扭矩/Screw torque	M3/0.4~0.7N.m
接线规格/Wiring specifications	2/0AWG or 70mm²
建议剥线长度/Suggested stripping length	19~21mm (Crimp type)
线径OD/Wire diameter	15.5~17mm (Crimp type)
额定电压/Rated voltage	1500V DC
额定电流/Rated current	250A
绝缘电阻/Insulate resistance	≥5000MΩ (drying)
耐电压/Withstanding voltage	6800V/min
接触电阻/Contact resistance	≤0.5mΩ
过电压等级/Overvoltage category	III
污染等级/Pollution degree	3
防护等级/Ingress protection	IP67(Mated)
使用温度范围/Operating temperature(°C)	-40~+125(including temperature rise)
盐雾/Salt spray	48h
储存温度/Storage temperature(°C)	-40~+85
阻燃等级/Flame retardant ability	UL94-V0
符合RoHS环保要求/Conform to RoHS	Yes
UL4128认证/UL4128 certification	E526028
TUV认证/TUV certification	50581738
满足户外使用/Satisfy outdoor use	Yes



ESS-250A-70-X-XX-XX

02: 负极
03: 正极
Color: BK : Black
OR : Orange
RD : Red
Contact Termination: B : Busbar
C : Crimp
S : Screw
B/S : Copper Screw

DEGSON		MATERIAL:	SURFACE/COLOR:
MAT NO./REV:		/	MAT STATUS:
APPD: 刘剑	2024.01.24	NAME	
CHKD: 于进海	2024.01.21	ESS-250A-70-X-XX-XX	
DRFT: 张晓瑶	2024.01.17	DRAWING NO.	TYPE
200270377	CUSTOMER DRAWING	DRAWING STATUS	SCALE
1:1	SHEET	1/1	

1

2

3

4

5

6