

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless express written authorization is granted. All rights reserved for patent, utility model or designs registrations. 非经书面明确授权, 否则禁止转让、复制、利用、交还本文档内容, 侵犯者将承担法律责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。

FOR-1755 Rev.1.3



2

3

4


5

6




Busbar  
(适配M5螺钉扭矩: 6N.m)

其他接线方式: 形式一:




Screw  
(锁合扭矩: 2-3N.m)


形式二:





仅Busbar的形式3D展示:



形式三:



Copper Screw  
(锁合扭矩: 6N.m)



Recommended  
Panel Cut-Out

| 尺寸公差(mm) |       |       |       |       | 0.05/10<br>±1' |
|----------|-------|-------|-------|-------|----------------|
| 0        | >30   | >60   | >100  | >150  |                |
| ~30      | ~60   | ~100  | ~150  | ~150  |                |
| ±0.20    | ±0.30 | ±0.50 | ±0.70 | ±1.00 |                |

| 技术要求/Technical requirements:                |                                      |
|---------------------------------------------|--------------------------------------|
| 颜色/Color                                    | Black, Orange, Red                   |
| 锁紧方式/Locking method                         | 卡扣(Buckle)                           |
| 接线方式/Terminal                               | Busbar, Screw, Crimp, Copper Screw   |
| 外壳材料/Housing material                       | PA+GF                                |
| 接触件材料/Connector material                    | 铜合金(Copper alloy)                    |
| 插入力/Insertion force                         | 100N Max                             |
| 拔出力/Withdrawal force                        | >10N                                 |
| 插拔次数/Mechanical working life(mating cycles) | 100                                  |
| 安装螺母紧固扭矩/Screw torque                       | M3/0.4~0.7N.m                        |
| 接线规格/Wiring specifications                  | 2/0AWG or 70mm²                      |
| 建议剥线长度/Suggested stripping length           | 19~21mm (Crimp type)                 |
| 线径OD/Wire diameter                          | 15.5~17mm (Crimp type)               |
| 额定电压/Rated voltage                          | 1500V DC                             |
| 额定电流/Rated current                          | 250A                                 |
| 绝缘电阻/Insulate resistance                    | ≥5000MΩ (drying)                     |
| 耐电压/Withstanding voltage                    | 6800V/min                            |
| 接触电阻/Contact resistance                     | ≤0.5mΩ                               |
| 过电压等级/Overvoltage category                  | III                                  |
| 污染等级/Pollution degree                       | 3                                    |
| 防护等级/Ingress protection                     | IP67(Mated)                          |
| 使用温度范围/Operating temperature(° C)           | -40~+125(including temperature rise) |
| 盐雾/Salt spray                               | 48h                                  |
| 储存温度/Storage temperature(° C)               | -40~+85                              |
| 阻燃等级/Flame retardant ability                | UL94-V0                              |
| 符合RoHS环保要求/Conform to RoHS                  | Yes                                  |
| UL4128认证/UL4128 certification               | E526028                              |
| TUV认证/TUV certification                     | 50581738                             |
| 满足户外使用/Satisfy outdoor use                  | Yes                                  |



ESS-250A-70-X-XX-XX

02: 负极  
03: 正极  
Color: BK : Black  
OR : Orange  
RD : Red  
Contact Termination: B : Busbar  
C : Crimp  
S : Screw  
B/S : Copper Screw

| DEGSON       |                  | MATERIAL:           | SURFACE/COLOR: |
|--------------|------------------|---------------------|----------------|
| MAT NO./REV: |                  | /                   | MAT STATUS:    |
| APPD: 刘剑     | 2024.01.24       | NAME                |                |
| CHKD: 于进海    | 2024.01.21       | ESS-250A-70-X-XX-XX |                |
| DRFT: 张晓瑶    | 2024.01.17       | DRAWING NO.         | TYPE           |
| 200270377    | CUSTOMER DRAWING | DRAWING STATUS      | SCALE          |
| 1:1          | SHEET            | 1/1                 |                |

1

2

3

4

5

6