





active

未注公差/General tolerances(mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	~2.50	±2°
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



4	Screw	Steel	M3/Zn Plated
3	Cage	Copper alloy	M3/Ni Plated
2	Pin header	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
------	--------------	----------	-------

UL 标准/UL Standard:

额定电压/电压/Rated Voltage(V)/Current(A)

IEC 标准/IEC Standard:

过压类别/Overvoltage Category/污染等级/Pollution Degree

额定电压/电压/Rated Voltage(V)/Current(A)

工频耐压/Withstanding voltage(V/1Min)

螺丝扭矩/Torque Tightening(N·m/Lb.in)

线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)

间距/Pitch(mm)/线数范围/Poles

剥线长度/Stripping length(mm)

使用温度范围/Operating temperature(°C)

符合RoHS环保要求/Conform to RoHS

Yes

MATERIAL: / SURFACE: /

MAT NO.: /

STATUS: /

APPD: LanCH 2020.03.21

CHKD: YuJZ 2020.03.21


DRFT: Jay.z 2018.10.22

DRAWING NO.: DG950-9.5-C01

REV T1

TYPE: CUSTOMER DRAWING SCALE: 2:1 SHEET 1/1

PCB LAYOUT



REV ECN DESCRIPTION DRFT DATE