







PCB LAYOUT



未注公差/General tolerances(mm)												
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20
												±2'



The first foot from the left side is rear



active

JL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	600/41	600/41	/
EC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	800/41	1000/41	1000/41
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8	8	8
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	24~8/0.2~6,10(sol)		
间距/Pitch(mm)/线数范围/Poles	7.5/N=02~12P		
剥线长度/Stripping length(mm)	11~13		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

REV	ECN	DESCRIPTION	DRFT	DATE
T1	20210085	1xAdd the UL lettering	Chen Zh	2021.05.10

MATERIAL:	/	SURFACE:	/
MAT NO.:			
STATUS:			
APPD:Lan ChH	2021.05.10	NAME:	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD
CHKD:Yu JZh	2021.05.10	NAME:	DEGSON®
DRFT:Liu ZhH	2020.01.02	NAME:	DG2206R-7.5-DB-XXP-1Y-00A(H)
SIZE: A4	mm (inch)	DRAWING NO.:	10001089
TYPE: CUSTOMER DRAWING	SCALE: 2:1	REV	T1
		SHEET	1/1