


H

1. Pitch: 3.5mm , Poles: XXP
2. Rated voltage/current: UL 300V/7A
 Δ VDE 450V/5A
3. Operation temperatures: -40℃ ~ +105℃
4. Withstanding Voltage: AC2500/1min
5. Insulation Resistance: 5000M Ω /DC1000V
6. Wire Range: 22~18AWG, 0.5mm² ~ 1.5mm²
7. Undimensioned Tolerances:

TOP VIEW-LAYOUT

I	DG250-3.5-Housing(自动化)	3018A0Y01C(H)	XX	PAG6	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTES
DETAILED LISTS			DFTO ZYH DATE: 12/24/08*		
	TOLERANCES EXCEPT AS NOTED		CHKD: Penny DATE: 11/6/12*		
	MM		MFD DATE:		
	.01 ±		APPVL: BJB DATE: 11/6/12*		
	.005 ±		MATERIAL :		
	ANGLES ± .1°		G.E :		
			FINISH:		
	THIRD ANGLE PROJECTION		SCALE : 1:1		
	DO NOT SCALE DRAWING			SHEET 1	OF 1
	NAME DG250-3.5-XXP-1Y-00A(H). (自动化)			DRAWING NO. DG250-3.5-E134	
			SIZE A4	REV T1 09/27/12*	