

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designer registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、商标、商号、名称、地址、电话、电邮、网址、域名、其他标识等权利外，其他权利均归本公司所有。未经许可，不得复制或传播。违者必究。

FOR-1755 Rev.1.7


2

3


4

5


6




N=2






N=3




N=even number: $5.08 \times (N/2 - 1) + 3.34$
N=odd number: $5.08 \times [(N-1)/2 - 1] + 3.34$



N>3



未注公差/General tolerances (mm)															0.1/10 ±2°
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500		
3	6	10	18	30	50	80	120	180	250	315	400	500	>500		
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50		



Note:

The A&Z(H) in the name means: A(H) and Z(H).

5	Screw	Steel	M3/Zn Plated
4	Clamp	Copper alloy	Sn Plated
3	Cage	Copper alloy	M3/Ni Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:		B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)		300/18	/	300/10
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2	II/2
额定电压/电压/Rated Voltage(V)/Current(A)		250/15	320/15	630/15
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		4	4	4
螺丝扭矩/Torque Tightening(N·m/Lb.in)		M3, 0.6/5.3		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)		30~12 / 0.2~2.5		
间距/Pitch(mm)/线数范围/Poles		5.08/N=02~24P		
剥线长度/Stripping length(mm)		7		
使用温度范围/Operating temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		

			MATERIAL:			SURFACE/COLOR:						
APPD: 兰春华			MAT NO./REV: - / 00			MAT STATUS: 批量						
CHKD: 龚耀志			NAME									
DRFT: 朱岳鹏			2EDGKJ-5.08-XXP-1Y-00A&Z(H)									
DATE			DRAWING NO.		TYPE		DRAWING STATUS		SCALE		SHEET	
2022.08.12			200103094		CUSTOMER DRAWING		已发布		2:1		1/1	
												



00	ECN	DESCRIPTION	DRFT	DATE
REV	ECN	DESCRIPTION	DRFT	DATE