

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、商标、名称权、商号权、域名权、其他知识产权等权利外，本公司保留对涉及发明、实用新型、外观设计、发明专利、软件著作权、商标、名称权、商号权、域名权、其他知识产权等权利的所有权利。

FOR-1755 Rev.1.7

2





3

4


5

6


PCB LAYOUT
10.0x(N-1)



Based on Cover, the first one is left pin header.



未注公差/General tolerances (mm)														0.1/10 ±2°
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	
3	6	10	18	30	50	80	120	180	250	315	400	500		
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



Note: The A&Z (H) in the name means: A(H) and Z(H).

6	Cover	PA66	UL94V-0
5	Housing 2	PA66	UL94V-0
4	Housing 1	PA66	UL94V-0
3	Spring	Stainless steel	/
2	Pin header 2	Copper	Sn plated
1	Pin header 1	Copper	Sn plated
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:		B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)		600/70	600/70	600/5
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)		1000/76	1000/76	1000/76
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		8	8	8
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)		20~4/ 0.2~16		
间距/Pitch(mm)/线数范围/Poles		10.0/N=02~12P		
剥线长度/Stripping length(mm)		17~18		
使用温度范围/Operating temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		



MATERIAL: -	SURFACE/COLOR:
MAT NO./REV: - / 00	MAT STATUS: 批量

APPD: 兰春华	2022.08.19	NAME	DG271V-10.0-DA-XXP-1Y-100A&Z(H)		
CHKD: 陈招	2022.08.19				

00			袁路易	2022.08.19	DRFT: 袁路易	2022.08.19	DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
REV	ECN	DESCRIPTION	DRFT	DATE	① ② A4	③ (inch)	200022096	CUSTOMER DRAWING	已发布	1.2:1	1/1

1

2

3

4

5

6