

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless and until authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、集成电路布图设计专有权、其他知识产权等权利外，本公司保留所有权利。 未经授权，不得复制或传播本文件内容。 未经本公司书面许可，不得将本文件内容用于任何目的。

FOR-1755 Rev.1.7

2







3

4

5

6

PCB LAYOUT



5	Small Pin header	Copper alloy	Sn plated
4	Big Pin header	Copper alloy	Sn plated
3	Cover	PA66	UL94V-0
2	Button	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:		B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)		300/8	150/8	300/8
IEC 60947-7-4标准/IEC 60947-7-4 Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)		320/10	320/10	630/10
额定脉冲电压(KV)/Rate Impulse Voltage(KV)			4	
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG mm²)		22~ 16/ 0.2~ 1.5		
IEC 60998 标准/IEC 60998 Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)		/	450/10	/
工频耐压/VWithstanding voltage(V/1Min)		AC2500		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG mm²)		22~ 16/ 0.2~ 0.75		
间距/Pitch(mm)/线数范围/Poles		3.5/N= 02~ 24P		
剥线长度/Stripping length(mm)		8.5~ 9.5		
使用温度范围/Operating temperature(°C)		-40~ + 105		
符合 RoHS 环保要求/Conform to RoHS		Yes		

active

02		1X 出脚公差调整	裴徐涛	2023.10.26
REV	ECN	DESCRIPTION	DRFT	DATE

MATERIAL:		SURFACE/COLOR:	
MAT NO./REV:		MAT STATUS: 批量	
APPD: 兰春华	2023.10.26	NAME	
CHKD: 陈招	2023.10.26	DRAWING NO.	
DRFT: 裴徐涛	2023.10.26	TYPE	
DRAWING NO.		DRAWING STATUS	
200029000		已发布	
TYPE		SCALE	
CUSTOMER DRAWING		3:1	
SHEET		1/1	