









未注公差/General tolerances (mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
3	6	10	18	30	50	80	120	180	250	315	400	500		±2°
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	

PCB LAYOUT



Note:

The A&Z (H) in the name means: A(H) and Z(H).

2	Pin header	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/8	/	300/8
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	250/7	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	2.5	/
间距/Pitch(mm)/线数范围/Poles	3.81/N=02~24P		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		



MATERIAL:	SURFACE/COLOR:
MAT NO./REV: - / 00	MAT STATUS: 批量

APPD: 兰春华	2022.11.07	NAME	15EDGB-3.81-XXP-1Y-00A&Z (H)		
CHKD: 龚耀志	2022.11.04				

DRFT: 周锡锦	2022.11.04	DRAWING NO.	200021178	TYPE	CUSTOMER DRAWING	DRAWING STATUS	已发布	SCALE	2:1	SHEET	1/1
-----------	------------	-------------	-----------	------	------------------	----------------	-----	-------	-----	-------	-----

00			周锡锦	2022.11.04
REV	ECN	DESCRIPTION	DRFT	DATE