

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、商标、商号、名称、域名、其他知识产权等权利外，本公司保留对设计及其使用、复制、分发、修改、传播、销售、租赁、出借、转让、许可、其他知识产权等权利的所有权利。

FOR-1755 Rev.1.7







2

3



4

5

6




active



E

4:1



UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/30	150/30	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	500/32	800/32	800/32
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	4	4	4
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M3, 0.8/7.02		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	28~10 / 0.2~6.0(sol) 28~10 / 0.2~4.0(str)		
间距/Pitch(mm)/线数范围/Poles	10.0/N=01P		
剥线长度/Stripping length(mm)	8~9		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

			MATERIAL:		SURFACE/COLOR:		
			MAT NO./REV: - / 00		MAT STATUS: 批量		
APPD:	蓝贵凡	2023.05.08	NAME				
CHKD:	曹利彬	2023.05.08	DGP4-01P-1Y-00Z (H)				
DRFT:	姜民洁	2023.05.08					
 A4			DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
 (inch)			200124471	CUSTOMER DRAWING	已发布	2:1	1/1

00			姜民洁	2023.05.08
REV	ECN	DESCRIPTION	DRFT	DATE

1

2

3

4

5

6