

FOR-1761 Rev. 1.7

2

3

4

5

6

7

8

9

10

11

12

Reel Name	POLE	Width/W	Pitch/P	Width/F	Width/Bo	Qty. pre reel	Reel qty. per carton	Qty. per carton
2EDGVM-THR-5, 08-REEL (32)	2`3	32mm	20mm	14.25mm	20.61mm	140	8	1120
2EDGVM-THR-5, 08-REEL (56)	4`8	56mm	20mm	26.25mm	38.67mm	140	5	700
2EDGVM-THR-5, 08-REEL (88)	9`12	88mm	20mm	42.25mm	73.21mm	140	3	420

SCALE: 1:1

REELING DIRECTION

WITHOUT CHARGE WITH CHARGE WITHOUT CHARGE

10 PCS XX PCS 10 PCS 50 mm

W F P B0

Pad of single pole product putting direction

Pad of double pole product putting direction

The reel drawing just reference only

PCB LAYOUT

14.7

8.6

12

13

2.6±0.3

3.9

3

1

2

3.94

5.08

5.08x(N-1)

5.08xN+2.8

1

active

UL 标准/UL Standard		B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)		300/15	/	300/10
EC 标准/EC Standard				
UL 污染等级/Contamination Category (°)/污染等级/ Pollution Degree		III/3	III/2	II/2
额定电压/电压/Rated Voltage(V)/Current(A)		320/20	/	/
额定脉冲电压/电压/Rate Impulse Voltage(KV)		4	/	/
焊脚/Pin(mm)/线数范围/Range/ Poles		5.08N-02-12P		
使用温度范围/Operating temperature(°C)		40°-+120		
符合RoHS环保要求/Conform to RoHS		Yes		
标准颜色编号/Standard color number: PANTONE /RAL		/		

Material:

Surface Color:

MAT. NO. /REV: - 00

MAT. STATUS: 数量

2EDGVC-THR-5, 08-XP-1Y-00A&Z (H)

200019800

CUSTOMER DRAWING

已发布

4:1

1/1