



Specifications:

Current rating:1.0AAC/DC

Voltage rating:250V AC/DC Δ

Contact resistance:20m ohm max.

Withstanding Voltage:500V AC/minute

Insulation resistance:1000M ohm min.

Temperature Rating:-40°C ~ +105°C

Materials:

Insulator:PBT (UL94V-0)

Contact:Copper Alloy

Finish:Selective Gold Plated

How To Order

4401-XXSR-XX

Blank:Black(Standard Color)
GR;Gray;BU:Blue
SR:With Strain Relief
No. of Contacts

Dimension Information: Δ

Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B
6	12.30	5.08	30	42.78	35.56
8	14.84	7.62	34	47.86	40.64
10	17.38	10.16	36	50.40	43.18
12	19.92	12.70	40	55.48	48.26
14	22.46	15.24	44	60.56	53.34
16	25.00	17.78	50	68.18	60.96
18	27.54	20.32	56	75.80	68.58
20	30.08	22.86	60	80.88	73.66
24	35.16	27.94	64	85.96	78.74
26	37.70	30.48			

RoHS Compliant

				DRAWN: Leo	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15	Neltron Industrial Co., Ltd.	
G	18-Dec-2019	modify tolerance	Jamie	CHECKED: Jeremy Liu	UNIT: mm	DESCRIPTION: 2.54MM Flat Cable IDC Socket With Strain Relief	SIZE A4
F	30-Oct-2013	ECN-CN1310004	Andrew		SCALE: 1:1		
E	04-Dec-2008	ECN-CN081211	zhangxh	APPROVAL: MIKE WU	SHEET: 1 / 1	PART NO: 4401-XXSR-XX	
D	11-Sep-2008	ECN-CN080916	Leo		PROJECTION:		
A	10-MAR-2008		Leo				
REV	DATE	FILE	BY				