



**Highlights**

- 1 to 24 poles
- Vertical pin strip
- Spacing 5.08 mm
- Inverted mating face
- Suitable for Board-to Board contacting

**Wire Sizes**

Solid min	-
Solid max	-
Stranded (flexible) min	-
Stranded (flexible) max	-
Stranded with ferrule min	-
Stranded with ferrule max	-

**Dimensions**

PCB hole diameter	1.4 mm
-------------------	--------

**Materials**

Contact spring	Bronze
----------------	--------

**Insulating Material**

Material	PA 6.6
Flammability class	UL 94 V-0

**Temperatures**

Operating temperature	-40 °C (without mech. load) - 105 °C
Store temperature	-40 °C - 105 °C

**Wave Soldering Process**

Soldering temperature, recommended	260 °C
Peak soldering time, recommended	3-4 s

**Reflow Process**

Soldering temperature, recommended	-
Peak soldering time, recommended	-



Technical Data // **STLZ950/..-5.08-V-GREEN-INV**

Spacing 5.08 mm

**Colours**

GREEN, RAL 6018

LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions.  
Special colours on request.

**Ratings**

UseGroup	c  US			
	B	C	D	
Rated voltage	300 V	-	300 V	250 V
Rated current	15 A	-	10 A	12 A
Overvoltage category				III
Test voltage	1.60 kV	-	1.60 kV	4.0 kV
Pollution degree				3

**Counterparts (Spacing 5.08 mm)**

Pin Strip/Terminal Block

STLZ950	STLZ990	STLZ970	AKZ950	AKZS950
---------	---------	---------	--------	---------

In combination of connectors with different admission data, the lower value is valid.

**Accessoires**

Figure	Designation	Article Number
	Coding Star CS4-5.0/5.08-RED	Art.-Nr. 50000000026

Spacing 5.08 mm

**Order Data (Spacing 5.08 mm)**

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	12.16	STLZ950/2-5.08-V-GREEN-INV	50950029121 F	200
3	17.24	STLZ950/3-5.08-V-GREEN-INV	50950039121 F	200
4	22.32	STLZ950/4-5.08-V-GREEN-INV	50950049121 F	200
5	27.40	STLZ950/5-5.08-V-GREEN-INV	50950059121 E	100
6	32.48	STLZ950/6-5.08-V-GREEN-INV	50950069121 E	100
7	37.56	STLZ950/7-5.08-V-GREEN-INV	50950079121 E	100
8	42.64	STLZ950/8-5.08-V-GREEN-INV	50950089121 D	50
9	47.72	STLZ950/9-5.08-V-GREEN-INV	50950099121 D	50
10	52.80	STLZ950/10-5.08-V-GREEN-INV	50950109121 D	50
11	57.88	STLZ950/11-5.08-V-GREEN-INV	50950119121 D	50
12	62.96	STLZ950/12-5.08-V-GREEN-INV	50950129121 D	50
13	68.04	STLZ950/13-5.08-V-GREEN-INV	50950139121 D	50
14	73.12	STLZ950/14-5.08-V-GREEN-INV	50950149121 D	50
15	78.20	STLZ950/15-5.08-V-GREEN-INV	50950159121 D	50
16	83.28	STLZ950/16-5.08-V-GREEN-INV	50950169121 D	50
17	88.36	STLZ950/17-5.08-V-GREEN-INV	50950179121 D	50
18	93.44	STLZ950/18-5.08-V-GREEN-INV	50950189121 D	50
19	98.52	STLZ950/19-5.08-V-GREEN-INV	50950199121 D	50
20	103.60	STLZ950/20-5.08-V-GREEN-INV	50950209121 D	50
21	108.68	STLZ950/21-5.08-V-GREEN-INV	50950219121 D	50
22	113.76	STLZ950/22-5.08-V-GREEN-INV	50950229121 D	50
23	118.84	STLZ950/23-5.08-V-GREEN-INV	50950239121 D	50
24	123.92	STLZ950/24-5.08-V-GREEN-INV	50950249121 D	50



Spacing 5.08 mm

Technical drawing

