








未注公差/General tolerances(mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	~2.50	±2'
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



6	Spring	Stainless Steel	
5	Clamp	Copper alloy	Sn plated
4	Housing2	PA66	UL94V-0
3	Housing1	PA66	UL94V-0
2	Side Housing	PA66	UL94V-0
1	Cover	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
额定电压/电压/Rated Voltage(V)/Current(A)		300/15	150/15
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2
额定电压/电压/Rated Voltage(V)/Current(A)		320/20	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		4	/
螺丝扭矩/Torque Tightening(N·m/Lb.in)			/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)			0.2~2.5/22~14
间距/Pitch(mm)/线数范围/Poles			5.08/N=02~24P
剥线长度/Stripping length(mm)			9~10
使用温度范围/Operating temperature(°C)			-40~+105
符合RoHS环保要求/Conform to RoHS			Yes
标准颜色编号/Standard color number:			PANTONE 428C

MATERIAL: /	SURFACE: /
MAT NO.: /	NAME: 8EDGK-5.08-XXP-11-1001A(H)
STATUS: /	DRAWING NO: 8EDGK-5.08-1000-C02
APPD: /	REV: TO
CHKD: /	SCALE: 1:1
DRFT: WangY1 2020.06.01	SHEET: 1/1
SIZE: A4	TYPE: CUSTOMER DRAWING

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------