



WILLAS



100mA SMALL SIGNAL SWITCHING DIODE - 90V
SOD-323 PACKAGE

1SS355

• Applications

High speed switching

• Features

- 1) Small surface mounting type.
- 2) High Speed.(trr =1.2ns Typ.)
- 3) High reliability with high surge current handling capability.
- 4) RoHS product for packing code suffix "G",
Halogen free product for packing code suffix "H".
- 5) Weight :0.01g



• Construction

Silicon epitaxial planar

Moisture Sensitivity Level 1

• Device Marking and Ordering Information

Device	Marking	Shipping
1SS355	5D	3000/Tape&Reel



• Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Peak reverse voltage	V_{RM}	90	V
DC reverse voltage	V_R	80	V
Peak forward current	I_{FM}	225	mA
Mean rectifying current	I_O	100	mA
Surge current (1s)	I_{surge}	500	mA
Junction temperature	T_J	125	°C
Operating/Storage temperature	T_{stg}	-55~+125	°C

• Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditons
Forward voltage	V_F	—	—	1.2	V	$I_F=100mA$
Reverse current	I_R	—	—	0.1	μA	$V_R=80V$
Capacitance between terminals	C_T	—	—	3.0	pF	$V_R=0.5V, f=1MHz$
Reverse recovery time	t_{rr}	—	—	4	ns	$V_R=6V, I_F=10mA, R_L=100\Omega$



• Electrical characteristic curves ($T_a=25^\circ\text{C}$)




Fig.1 Forward characteristics




Fig.2 Reverse characteristics




Fig.3 Capacitance between terminals characteristics




Fig.4 Reverse recovery time characteristics




Fig.5 Surge current characteristics





Fig.6 Reverse recovery time (t_R) measurement circuit



Outline Drawing

SOD-323



Dimensions in inches and (millimeters)



WILLAS



100mA SMALL SIGNAL SWITCHING DIODE - 90V
SOD-323 PACKAGE

1SS355

Ordering Information:

Device PN	Packing
1SS355-T ⁽¹⁾ G ⁽²⁾ -WS	Tape&Reel: 3 Kpcs/Reel

Note: (1) Packing code, Tape&Reel Packing

(2) RoHS product for packing code suffix "G" ; Halogen free product for packing code suffix "H"

Disclaimer

WILLAS reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. WILLAS or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on WILLAS data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. WILLAS does not assume any liability arising out of the application or use of any product or circuit.

WILLAS products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of WILLAS. Customers using or selling WILLAS components for use in such applications do so at their own risk and shall agree to fully indemnify WILLAS Inc and its subsidiaries harmless against all claims, damages and expenditures.