








未注公差/General tolerances(mm)

0 ~3	>3 ~6	>6 ~10	>10 ~18	>18 ~30	>30 ~50	>50 ~80	>80 ~120	>120 ~180	>180 ~250	>250 ~315	>315 ~400	>400 ~500	>500 ~2.50	0.1/10 ±2°
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



PCB LAYOUT



4	Cage	Copper Alloy	M3.5/Ni Plated
3	Pin Header	Copper	Sn Plated
2	Screw	Steel	M3.5/Zn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/30	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	II/2	III/2	III/3
额定电压/电流/Rated Voltage(V)/Current(A)	1000/32	630/32	500/32
额定脉冲电压(kV)/Rate Impulse Voltage(kV)		6.0	
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M3.5: 0.57/5.0, ≥03P: 0.8/7.02		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~4/6(sol)/30~10		
间距/Pitch(mm)/线数范围/Poles	6.35/N=02~24P		
剥线长度/Stripping length(mm)	8~9		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Confirm to RoHS	Yes		

MATERIAL:	/	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
MAT NO.:	/		
STATUS:	/	NAME: DG636S-6.35-XXP-1Y-00A(H)	
APPD: Lan ChH 2020.05.16		DRAWING NO.: DG636S-6.35-C01	
CHKD: Yu JZh 2020.05.16		REV: T1	
DRFT: BYH 2018.07.04		SHEET: 1/1	
REV	ECN	DESCRIPTION	DRFT
DATE			
SIZE: A4	mm (inch)	TYPE: CUSTOMER DRAWING	SCALE: 2:1