



02P




03P



未注公差/General tolerances(mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	~2.50	±2'
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	

PCB LAYOUT

Bending the pin-header
after assembling

6	Right housing	PA66	UL94V-0
5	Clamp	Copper alloy	Sn Plated
4	Left housing	PA66	UL94V-0
3	Housing2	PA66	UL94V-0
2	Side Housing1	PA66	UL94V-0
1	Housing1	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
------	--------------	----------	-------

UL 标准/UL Standard:

额定电压/电压/Rated Voltage(V)/Current(A)

IEC 标准/IEC Standard:

过压类别/Overvoltage Category/污染等级/Pollution Degree

额定电压/电压/Rated Voltage(V)/Current(A)

额定脉冲电压(KV)/Rate Impulse Voltage(KV)

线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)

间距/Pitch(mm)/线数范围/Poles

剥线长度/Stripping length(mm)




使用温度范围/Operating temperature(°C)

符合RoHS环保要求/Conform to RoHS

标准颜色编号/Standard color number:

PANTONE / RAL

PANTONE 428C

The first pin will
bulge to the up

MATERIAL: / SURFACE: /

MAT NO.: /

STATUS: /

APPD: /

CHKD: /

DRFT: WangY1 2020.06.19

DRAWING NO.: 8EDGCM-7.5-C02

TYPE: CUSTOMER DRAWING

SCALE: 2:1

SHEET 1/1