



单位:微米/General tolerance(μm)										
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250
~	~	~	~	~	~	~	~	~	~	~
3	6	10	18	30	50	80	120	180	250	315
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.60
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.60

4	Pin header	Copper alloy	Sn Plated
3	Cage	Copper alloy	M3/Ni Plated
2	Screw	Copper alloy	M3/Ni Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	
UL 标准 / UL Standard:		B	C
额定电压 / 电压 / Rated Voltage(V) / Current(A)		600/30	600/30
EC 标准 / EC Standard:		D	
过电压类别 / Overvoltage Category / 污染等级 / Pollution Degree		III/2	
额定电压 / 电压 / Rated Voltage(V) / Current(A)		800/32	
工频耐压 / Withstanding voltage		AC 35 00V/1 min	
螺栓扭矩 / Torque Tightening(N		m(Lb.in)	M3, 0.5/4.43
线径范围 / 线径和线径 / Wire Range(rigid and flexible)(mm² / AWG)			0.2-4.0/30-10
间距 / Pitch(mm)		极数范围 / Poles	7.5/02P
剥线长度 / Stripping length(mm)			10
使用温度范围 / Operating temperature(°C)			-40~+105
符合RoHS环保要求 / Conform to RoHS			Yes
标准颜色编号 / Standard color number: RAL			RAL 2000

MATERIAL:	/	SURFACE:	/
MAT NO.:	/	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS:	/	NAME:	
APPD:	/	TSCK4-02P-15-01A(H)	
CHKD:	/	DRAWING NO.:	
DRFT:	CenMZ 220.05.19	TSCK4-C02	
SIZE:	A4	REV	
TYPE:	CUSTOMER DRAWING	TO	
SCALE:	1:5:1	SHEET	
		1/1	